



HONDA PIONEER 700™ SIDE ENCLOSURES

Installation Instructions

1. From side of PIONEER®, install side cover against roll cage/frame so straps will engage roll bar along the top, rear and sides. Covers will attach to outside edge of roll cage and should be level and straight with cage frame. Repeat for other side.
2. Zip Doors in place. (1 left, 1 right)
3. Before supplied Velcro® can be installed, you must clean areas with alcohol.
4. Install supplied Velcro® around sides and door openings corresponding to Velcro® mate on cover if desired. To be able to open doors easier do not install adhesive Velcro to doors so the elastic can move as the door opens and closes. If you need the doors to seal completely you can install Velcro but need to unzip door almost completely each time door opens.
5. Attach bottom of side enclosure zippered door to plastic on top of doors. Doors will be able to be opened while attached to doors if zipper is unzipped to where window turns down along windshield as shown in image below right. Attach plastic clips and clamps as necessary to achieve a tight fit.

Your new cover is guaranteed against any defects in material and workmanship for 1 year from the date of purchase. Should any problems arise, please contact your dealer. No warranty card is necessary.



Your UTV has several warning and caution labels around the machine that may be covered when this cover is installed. It is your responsibility as the UTV owner to read and understand these warnings as well as making sure anyone who operates the UTV is aware of the proper operation.